

RATINGS FOR ATEX

Terminal	Rated Voltage	Maximum Rated Current	Conductor Size (sq mm) F=>Flexible R=>Rigid	Torque
KUT 2.5	750 V	24 A	Rated c/s 2.5 ▲ 0.5 - 2.5 F ▲ 0.5 - 4 R	0.5 Nm
KUT 4	750 V/550 V-TS32	32 A	Rated c/s 4 ▲ 0.5 - 4 F ▲ 0.5 - 6 R	0.5 Nm
KULT 4	750V	32 A	Rated c/s 4 ▲ 0.5 - 4 F ▲ 0.5 - 6 R	0.5 Nm
KUT 6	750 V/550 V-TS32	41 A	Rated c/s 6 ▲ 0.5 - 6 F ▲ 0.5 - 10 R	0.8 Nm
KULT 6	750 V	41 A	Rated c/s 6 ▲ 0.5 - 6 F ▲ 0.5 - 10 R	1.4 Nm
KUT 10	550 V	57 A	Rated c/s 10 ▲ 1.5 - 10 F ▲ 1.5 - 16 R	1.2 Nm
KULT 1	1000 V/750 V-TS32	57 A	Rated c/s 10 ▲ 1.5 - 10 F ▲ 0.5 - 16 R	1.5 Nm
KUT 16	750 V	76 A	Rated c/s 16 ▲ 6 - 16 F ▲ 6 - 25 R	1.2 Nm
KUT 25	750 V	101 A	Rated c/s 25 ▲ 6 - 16 F ▲ 6 - 25 R	2.3 Nm
KUT 35	750 V	125 A	Rated c/s 35 ▲ 10 - 35 F ▲ 10 - 35 R	3.0 Nm
KUT 50	1000 V	150 A	Rated c/s 50 ▲ 16 - 50 F ▲ 16 - 70 R	8.0 Nm
KUT 95	1000 V	232 A	Rated c/s 95 ▲ 25 - 95 F ▲ 25 - 120 R	20 Nm
MBT 4	420 V	24 A	Rated c/s 2.5 ▲ 0.5 - 2.5 F ▲ 0.5 - 4 R	0.5 Nm
KUDD 4	275 V	21 A	Rated c/s 2.5 ▲ 0.5 - 2.5 F ▲ 0.5 - 4 R	0.4 Nm
KU2D4	275 V	21 A	Rated c/s 2.5 ▲ 0.5 - 2.5 F ▲ 0.5 - 4 R	0.4 Nm
KU2D 4S	275 V	21 A	Rated c/s 2.5 ▲ 0.5 - 2.5 F ▲ 0.5 - 4 R	0.4 Nm
DU3D 4	275 V	18 A	Rated c/s 2.5 ▲ 0.5 - 2.5 F ▲ 0.5 - 4 R	0.5 Nm
DUSD 4	275 V	18 A	Rated c/s 2.5 ▲ 0.5 - 2.5 F ▲ 0.5 - 4 R	0.5 Nm
KUTSD 6	550 V	35 A	Rated c/s 6 ▲ 0.5 - 6 F ▲ 0.5 - 10 R	1.4 Nm
KSTD6WS	550 V	41 A	Rated c/s 6 ▲ 0.5 - 6 F ▲ 0.5 - 10 R	0.8 Nm
KUTD 10	420 V	61 A	Rated c/s 10 ▲ 1.5 - 10 F ▲ 1.5 - 16 R	1.2 Nm
KAT M4	750 V	57 A	Rated c/s 10 ▲ 0.5 - 10 F ▲ 0.5 - 10 R	1.2 Nm
KBT M4	750 V	57 A	Rated c/s 10 ▲ 0.5 - 10 F ▲ 0.5 - 10 R	1.2 Nm
KAT M5	750 V	76 A	Rated c/s 16 ▲ 0.5 - 16 F ▲ 0.5 - 16 R	2.0 Nm
KBT M5	750 V	76 A	Rated c/s 16 ▲ 0.5 - 16 F ▲ 0.5 - 16 R	2.0 Nm
DPBB 70	1000 V	192 A	Rated c/s 70 ▲ 10 - 70 F ▲ 10 - 70 R	3.0 Nm
KUDF 4	420 V	6.3 A	Rated c/s 2.5 ▲ 0.5 - 2.5 F ▲ 0.5 - 4 R	0.4 Nm
KUDDF 4	420 V	6.3 A UT / 20 A LT	Rated c/s 2.5 ▲ 0.5 - 2.5 F ▲ 0.5 - 4 R	0.4 Nm
UBDF 4	750 V	6.3 A	Rated c/s 4 ▲ 0.5 - 4 F ▲ 0.5 - 6 R	0.5 Nm
KUFH 4	750 V	6.3 A	Rated c/s 4 ▲ 0.5 - 4 F ▲ 0.5 - 6 R	0.5 Nm
KUF 10	750 V	10 A	Rated c/s 10 ▲ 0.5 - 10 F ▲ 0.5 - 10 R	1.4 Nm
KULTD 6	550 V*	32 A	Rated c/s 6 ▲ 0.5 - 6 F ▲ 0.5 - 10 R	1.0 Nm
KLTD M4	750 V	32 A	Rated c/s 6 ▲ 0.5 - 6 F ▲ 0.5 - 6 R	2.0 Nm
SUT 4	420 V	24 A	Rated c/s 2.5 ▲ 0.5 - 2.5 F ▲ 0.5 - 4 R	0.5 Nm
NET 4	420 V	32 A	Rated c/s 4 ▲ 0.5 - 4 F ▲ 0.5 - 4 R	0.5 Nm
PET 4	420 V	30 A	Rated c/s ▲ 0.5 - 4 F ▲ 0.5 - 4 R	0.5 Nm
DPBB50	1000 V	150 A	Rated c/s 50 ▲ 10 - 50 F ▲ 10 - 50 R	3.0 Nm
DPBB120	1000 V**	250 A	Rated c/s 120 ▲ 25 - 120 F ▲ 25 - 120 R	6.0 Nm
CST 70BB	750 V**	192 A	Rated c/s 70 F & R	6.0 Nm
CST 185BB	750 V**	353 A	Rated c/s 185 F & R	14 Nm
ET 6	-	-	Rated c/s 6 ▲ 1.5 - 6 F ▲ 1.5 - 10 R	0.8 Nm
ET 10	-	-	Rated c/s 10 ▲ 1.5 - 10 F ▲ 1.5 - 16 R	1.2 Nm
ET 16	-	-	Rated c/s 16 ▲ 6 - 16 F ▲ 6 - 25 R	1.2 Nm
ET 35	-	-	Rated c/s 35 ▲ 6 - 35 F ▲ 6 - 35 R	3.0 Nm
EBT 2.5	-	-	Rated c/s 2.5 ▲ 0.5 - 2.5 F ▲ 0.5 - 4 R	0.5 Nm
EBT 4	-	-	Rated c/s 4 ▲ 0.5 - 4 F ▲ 0.5 - 6 R	0.5 Nm
EBT 6	-	-	Rated c/s 6 ▲ 1.5 - 6 F ▲ 1.5 - 10 R	1.2 Nm
EBT 4 TWIN	-	-	Rated c/s 4 ▲ 0.5 - 4 F ▲ 0.5 - 6 R	0.5 Nm

* Without test probes

** With partition plate/end plate