

DISCRETE LED's

Part No.	Size	Colour	Water-clear or Diffused	Wave Length (nm)	Luminous Intensity IF=10mA(mcd), *IF=20mA(mcd)			Viewing Angle	Case Style	Diagram of the different Styles
					Min.	Typ.	Max.			

3mm STANDARD LED's

A30D060-22-U	3mm	Super-Red	Diffused	625nm	12.5	22	32	60°	2
B34D060-2-U	3mm	Flashing Red	Diffused	-	1.3	2	3.2	60°	2
A30D060-12-G	3mm	Green	Diffused	565nm	5	12	20	60°	2
A30D060-12-Y	3mm	Yellow	Diffused	590nm	5	12	20	60°	2
A30D060-30-N	3mm	Pure-Orange	Diffused	610nm	10	30	50	60°	2

3mm SUPER BRIGHT LED's

A32D060-250-M	3mm	Ultra-Red	Diffused	660nm	200	250	300	60°	2
A32W050-700-M	3mm	Ultra-Red	Water clear	660nm	500	600	700	30°	1
A32W050-1300-M	3mm	Ultra-Red	Water clear	660nm	1100	1200	1300	30°	1
A32W050-200-G	3mm	Green	Water clear	565nm	100	200	300	30°	1
A32W050-750-K	3mm	Yellow	Water clear	590nm	400	750	1300	50°	1
Z36W030-550-T	3mm	Blue-Green	Water clear	505nm	500	550	600	50°	3

3mm SUPER BRIGHT LED's

A32W050-600-M	3mm	Ultra-Red	Clear		500	600	700	50°	2
A32W050-1200-M	3mm	Ultra-Red	Clear		1100	1200	1300	50°	2
A32C050-30-Y	3mm	Yellow	Colour Clear		50	75	100	50°	2
A32C050-75-N	3mm	Orange	Colour Clear		200	300	400	50°	2

4mm SUPER BRIGHT LED's

C461MHR-495G	4mm	Hi-Red	Clear		102	180	280	95°	3
C461MPG-495G	4mm	Green	Clear		102	280	390	95°	3
C461MYL-495G	4mm	Yellow	Clear		102	280	380	95°	3
C461MBL-495G	4mm	Blue	Clear		26,6	80	102	96°	3

5mm STANDARD LED's

A53D060-50-U	5mm	Super-Red	Diffused	625nm	20	50	80	60°	4
A53D060-50-G	5mm	Green	Diffused	565nm	20	50	60	60°	4
A53D060-14-Y	5mm	Yellow	Diffused	590nm	5	14	32	60°	4
A53D060-46-N	5mm	Pure-Orange	Diffused	610nm	12	46	80	60°	4
A53D060-40-B	5mm	Blue	Diffused	430nm	20	40	60	60°	4
M59RG-CA-D	5mm	Red	White	625nm	3.2	5	8	60°	5
Bi-colour		Green	Diffused	565nm	3.2	5	8		
M59RG-CC-D	5mm	Red	White	660nm	100	200	300	60°	5
Bi-colour		Green	Diffused	565nm	40	60	80		

5mm SUPER BRIGHT LED's

A53D060-250-M	5mm	Ultra-Red	Diffused	660nm	200	250	300	60°	4
A53W030-200-G	5mm	Green	W-clear	565nm	100	200	300	30°	4
A53W030-850-K	5mm	Super/Yellow	W-clear	585-590	400	850	1300	30°	4

5mm SUPER BRIGHT LED's

C503AHR-115Q	5mm	Hi-Red	Clear	624	8200	11000	12000	15°	4
C512MHR-125Q	5mm	Hi-Red	Clear	-	770	1135	1500	25°	4
C503AHR-230Q	5mm	Hi-Red	Clear	624	2130	3500	5860	30°	4
C503MBG-115Q	5mm	Green	Clear	-	1520	2260	3000	15°	4
C503TPG-115Q	5mm	P.Green	Clear	527	12000	17500	23000	15°	4
C503AYL-115Q	5mm	Yellow	Clear	591	8200	16000	23500	15°	4
C503NBL-115Q	5mm	Blue	Clear	470	700	900	1100	15°	4
C503PBL-115Q	5mm	P.Blue	Clear	470	2130	2800	3000	15°	4
C512MBL-125Q	5mm	Blue	Clear	470	320	390	550	25°	4
C512TWN-125Q	5mm	P.White	Clear	-	4180	5000	5860	25°	4

