

GREENLINE TIMER

AGLTDO-.... Delay on
AGLTFLS-.... Repeat
AGLTINT-.... Interval
 Voltages: 12, 24 or 110VAC/DC & 220VAC

The GREEN LINE range of timers are top quality and good value for money...

NO 11 PIN BASE

The omission of the 11 PIN BASE means a reduction in costs, vibration and contact problems. Direct connection to correct industrial terminals is sound engineering.

EASY TO TEST


Also easy to change (only 4 wires), and very reliable.

NO FINGER TROUBLE

Green Line offers the feature of "Set and Forget" and the adjustment potentiometer can be removed to prevent tampering.

LOW PROFILE

Typical 11 Pin systems need 150mm off the chassis, whereas the Green Line requires only 40mm, so a neater & lower cost box can be used.



GREENLINE ECONO TIMER

GMT2-12B 12V AC/DC
GMT2-24B 24V AC/DC
GMT2-48B 48V AC/DC
GMT2-220A 220V AC
GMT2-110A 110V AC

FEATURES:

- DIPSWITCH SELECTABLE FUNCTIONS
- DIPSWITCH SELECTABLE PRESENT TIMES
- BETTER THAN 2% ACCURACY
- SMALL FOOTPRINT + DIN RAIL MOUNTABLE
- LOW COST - HIGH RELIABILITY
- LED-RELAY STATE INDICATION
- CHANGE OVER RELAY CONTACTS WITH ARC PROTECTION

TIMER RANGES SELECTABLE:

1, 3, 5, 10, 15, 20, 30, 45 Sec + 1, 3, 5, 10, 15, 30, 45, 60 Minutes

FUNCTIONS:

DELAY ON OR INTERVAL

SPECIFICATIONS:

Supply Voltage	220V AC $\pm 10\%$
Current consumption	<26mA
Timing Accuracy	<2%
Relay contact rating	
Max continuous current	10A
Max switching voltage	30V DC, 250V AC
Max switching current	10A
Max switching power	240W, 1.2KVA

SPECIAL TIME INTERVALS AVAILABLE ON REQUEST FOR LARGE ORDERS.

