

# ASTrobe



## FEATURES

- HIGH SOUND OUTPUT (105dB@1m)
- LOW CURRENT CONSUMPTION
- 16 USER SELECTABLE TONES
- 4 USER SELECTABLE FLASH RATE
- HIGH BRIGHT RED LED's
- SUPPLY VOLTAGE 18-30VDC
- VOLUME CONTROL
- CUSTOM AND OVERRIDE TONES
- IP65 WEATHER PROOF VERSION

## DESCRIPTION:

This weatherproof Sounder/Strobe (waterproof with optional conduit back box) is design optimized for use in fire alarm systems, but can be used in most applications requiring high sound output, "attention grabbing" double flash and economic current draw.

A choice of 16 fully synchronized primary sounds can be selected together with 4 volume settings and 4 flash rates through dip-switch 1-8. An alternate continuous tone is available for selection on PCB terminals or by third wire remote control. Red is standard, however other colours can be done on special order.

Model	ASTrobe
Operating Voltage Range	18-30Vdc
Current Consumption	17mA (Dependant on Sound and flash rate)
Operating Temperature	-20°C to 70°C
Construction	Flame Retardant ABS/PC
Ingress Protection	IP43 (IP65 with conduit base)
Dimensions	Shallow Base- 95x120x100mm Deep Base- 110x120x100mm
Sound Output	105dB(A) at 24Vdc
Selectable Tones	16
Selectable Flash Rate	4



**MIMIC COMPONENTS cc**

17 Ramsay Street  
Booyens 2091  
Johannesburg South Africa

P.O. Box 38493  
Booyens 2016 South Africa  
e-mail: sales@mimic.co.za

Tel: +27 11 689 - 5700  
Fax: +27 11 493 - 8821  
www.mimic.co.za