

900 SERIES

A range of voltmeters, thermometers, dot matrix and graphic panels supplied with separate mounting bezel including window. For more demanding applications an IP67 / NEMA 4X bezel is available. All these units have a 76x44mm bezel & a 72x40mm cut-out.



Auto-ranging Multi-meter -
Fitted with optional IP67 Bezel

DMM 939

3¾ digit LCD, LED backlit
Selectable annunciators
Continuity beeper output
Digital hold
IDC ribbon cable connection

BEZ 900-IP

Replaces std bezel
Screw fixing
Alloy & glass construction
Bezel 80.5x48.5mm
Cut-out 72x40mm



4-20mA Loop Powered Meter
DPM 942

3½ digit LCD
Programmable decimal points
Two calibration pots (zero/span)
Screw terminal connection



DC Voltmeter
DPM 950

3½ digit LCD, LED backlit
Auto-zero, auto-polarity
IDC ribbon cable connection
Single rail version **DPM 950S**



DC Voltmeter
DPM 959B

3½ digit LED
Programmable decimal points
Auto-zero, auto-polarity
IDC ribbon cable connection



AC Voltmeter
DPM 970

3½ digit LCD, LED backlit
Digital hold
Screw terminal connection



Thermometer - Pt100 Type
DTM 910

3½ digit LCD, LED backlit
Single step calibration
Screw terminal connection



Thermometer - K-Type
DTM 995

3½ digit LCD, LED backlit
Cold junction compensation
Screw terminal connection

Temp. Probe **K-TYPE PROBE**



Dot Matrix Character Display
DMX 908

8 character x 2 line LCD
7.92mm character height
LED backlighting (50mA)
HD44780 compatible interface
Supply voltage 5V d.c.
Supply current 0.5mA
IDC ribbon cable connection



Dot Matrix Character Display
DMX 916

16 character x 2 line LCD
5.5mm character height
LED backlighting (50mA)
HD44780 compatible interface
Supply voltage 5V d.c.
Supply current 0.5mA
IDC ribbon cable connection



Dot Matrix Graphic Display
DMX 973B

100 x 32 pixel supertwist LCD
LED backlighting (50mA)
Epson SED 1530 controller
68XX, 80XX & serial interfaces
Supply voltage 5V d.c.
Supply current 100µA
IDC ribbon cable connection



Controller Card
DMX 04

Plugs into DMX 908/916
Compatible with most 1, 2 & 4 line character displays
Re-writable EEPROM memory
Stores up to 100 messages each up to 80 characters

PC cable **DMX-CABLE-SER**